



lubecore™



lubecore™ **STEADYLUBE™** **LITHIUM COMPLEX**

EPO

AUTOMATED LUBRICATION SYSTEM GREASE

GRAISSE AUTOMATISÉE DE SYSTÈME DE LUBRIFICATION

• THIS PRODUCT IS NOT WHMIS CONTROLLED •

- High Visibility Blue for Easy Visual Inspection
- Automated Lubrication System Compatible
- Meets and Exceeds OEM Requirements
- Excellent Mechanical Stability
- Oxidation & Corrosion Protection
- Water Resistance
- Resists Thinning or Hardening in Bearings
- Minimizing Leakage
- Superior Pumpability
- Will Not Alter or Harden in Storage

NEXT GENERATION AUTOMATED LUBRICATION

Lubecore Steadylube™ Lithium Complex EPO Grease is formulated with highly refined base oil and specialty additives to meet the severe requirements of your equipment.



Lubecore Steadylube Lithium Complex EPO grease is a robust multi purpose lubricant that is highly recommended for extended service in heavy-duty automotive, trucks, buses, farm, construction and mining equipment, high temperature wheel bearings, roller and ball bearings, electric motor bearings, release bearings, universal joints, chassis, fifth wheel as well as a host of other applications.

PERFORMANCE DATA		
NLGI GRADE	ASTM D-217	0
WORKED PENETRATION @ 25° C	ASTM D-217	375
THICKENER TYPE	DATA	LITHIUM COMPLEX
TEXTURE	VISUAL	SMOOTH, FLUID
COLOR	VISUAL	BLUE
DROPPING POINT	ASTM D-2265	500° F MIN
VISCOSITY @ 40° C, CST	ASTM D-445	150 - 180
WELD LOAD,kg	ASTM D-2596	315
TIMKEN OK LOAD	ASTM D-2509	60 LBS
RUST TEST	ASTM D-2596	PASS
OPERATING TEMPERATURE	DATA	-30C / 177C -22F / 351F



lubecore™
STEADYLUBE™
LITHIUM COMPLEX
SEMI-SYNTHETIC

EP2

AUTOMATED LUBRICATION SYSTEM GREASE

GRAISSE AUTOMATISÉE DE SYSTÈME DE LUBRIFICATION

• THIS PRODUCT IS NOT WHMIS CONTROLLED •

- High Visibility Red for Easy Visual Inspection
- Automated Lubrication System Compatible
- Meets and Exceeds OEM Requirements
- Longer Life than Typical Mineral Oil Based Lubricants
- Oxidation & Corrosion Protection
- Water Resistant
- Resists Thinning or Hardening in Bearings
- Minimizing Leakage
- Superior Pumpability
- Will Not Alter or Harden in Storage

NEXT GENERATION AUTOMATED LUBRICATION

Lubecore Steadylube™ Lithium Complex Semi-Synthetic EP2 Grease is formulated with highly refined semi-synthetic base oil and specialty additives to meet the severe requirements of your equipment.

Lubecore Steadylube Lithium Complex Semi-Synthetic EP2 grease is a robust multi purpose lubricant that is highly recommended for extended service in heavy-duty automotive, trucks, buses, construction and mining equipment, high temperature wheel bearings, roller and ball bearings, electric motor bearings, release bearings, universal joints, chassis, fifth wheel as well as a host of other applications.



PERFORMANCE DATA		
NLGI GRADE	ASTM D-217	2
WORKED PENETRATION @ 25° C	ASTM D-217	285
THICKENER TYPE	DATA	LITHIUM COMPLEX
TEXTURE	VISUAL	SMOOTH, TACKY
COLOR	VISUAL	RED
DROPPING POINT	ASTM D-2265	500° F MIN
VISCOSITY @ 40° C, CST	ASTM D-445	130
WELD LOAD,kg	ASTM D-2596	315
TIMKEN OK LOAD	ASTM D-2509	60 LBS
RUST TEST	ASTM D-2596	PASS
OPERATING TEMPERATURE	DATA	-34C / 204C -29F / 400F