

Why Lubecore? Pneumatic Single Line 210 Out-Spec Guide

Fact	Benefit	Lubecore Single Line 210	Graco Grease Jockey
Positive Inlet Pressure Top Spring	<ul style="list-style-type: none"> * Automatic self-purging/bleeding if pump runs empty * Allows for use of heavier grease and longer systems at lower temperatures 		
Brass Super Injectors	<ul style="list-style-type: none"> * Automatic self-purging/bleeding injectors * 30 bar/450 PSI reloading and compatible with EP2 grease in approved design / environment * Brass material means no corrosion of metering valves * Lowest maintenance cost and ease of identification 		
Makrolon® Reservoir	<ul style="list-style-type: none"> * Breakproof - no maintenance * Remains clear for life 		
Corrosion Resistant Mounting System	<ul style="list-style-type: none"> * No replacing pumps * Low maintenance * No galvanic corrosion of pump body 		
Stainless Steel Follower Plate with Leak Proof Red Silicon Seal	<ul style="list-style-type: none"> * Clear grease level indication * No grease funnelling or corrosion * Protects grease from moisture & dirt 		
Automatic Low Level Shut-Off Option	<ul style="list-style-type: none"> * Pump doesn't run empty * Never bleed the system * Save time and money 		
Pressurized Housing Between Cycles	<ul style="list-style-type: none"> * Positive pressure inhibits the entrance of foreign material 		
Casted Hard Anodized Aluminum Pump Housing	<ul style="list-style-type: none"> * No deformation at high temperature * No corrosion of pump housing 		
Optional Heavy Duty Inline Filter	<ul style="list-style-type: none"> * Prevents system clogging * Will stop an air operated fill gun 		
Adjustable Run and Pause Cycles – Per Minute	<ul style="list-style-type: none"> * Optimize grease consumption * Precision lubrication saves components 		
Computer Interfaced Timer Programming	<ul style="list-style-type: none"> * Prevents unauthorized tampering with timer settings 		
Real Time Electronic Performance Report	<ul style="list-style-type: none"> * Date and time documented performance reports * Holds mechanics accountable 		
Operator Communication Light / Test “Smart Switch”	<ul style="list-style-type: none"> * Confirmation of complete cycles * Easy in dash test switch * Save both time and money 		
LED Indicator Light at Deutsch® Connector	<ul style="list-style-type: none"> * Light will glow if there is power to the solenoid * Reduces system inspection time 		
Guaranteed Residual Program	<ul style="list-style-type: none"> * Guaranteed residual value of greasing system * Pump is built to outlast equipment * Recycle by reinstalling on next unit * Reduced environmental impact 		
Heavy Duty Deutsch® Electrical Connections	<ul style="list-style-type: none"> * Wire connections protected from environment - road salt & brine * Reduced maintenance 		
Korilla Line Option	<ul style="list-style-type: none"> * Extreme duty flex hose * No broken line maintenance required guaranteed 		



For more information, contact us!

7065 Twiss Road,
Campbellville ON
L0P 1B0

P: 905.878.8805

F: 905.878.3641

www.lubecore.com